

**HD**  
ready



## 42SRE1

- Screen Dimensions : 105 cm (42")
- Sunlight Readable
- Hotel Mode (restricts user settings)
- Ideally suited for 24/7 applications
- Extensive input & output terminals
- Impressive Picture Quality: HD Ready
- Fast image response times
- Suitable for Point of Sale, Shop Windows, Hotel lobbies and Digital Signage (Airports, Railway stations)

## 42SRE1

Model	42SRE1
EAN Code	4994334252807
Category	Professional LCD Monitor
Type	Liquid crystal display panel
Screen size (diagonal image)	42" (105 cm)
Active screen area (W x H)	93.0 x 52.3 cm
Aspect ratio	16 : 9
Resolution in pixels	1,366 x 768 (WXGA)
Pixel pitch	0.227 x 0.681 mm
Brightness	1500 cd/m with ideal conditions under sunlight
Contrast ratio	1,500 : 1
Viewing angle	178° (horizontal and vertical)
Response time	6 ms (grey to grey)
Grey scale value	8 bit
Number of colours	16.7 M
Colour Systems	PAL, NTSC3.58, SECAM
Computer compatibility	UXGA, WXGA, SXGA, XGA, SVGA, VGA
Input terminals	DVI-D (digital/HDCP) D-sub15 5 x BNC (RGBHV,Y-Pb/Cb-Pr/Cr) Component (Y,Pb,Pr) BNC (Video) RS232 (D-Sub 9 pin) 2 x RCA (R/L mono) for Audio 3.5 mm Stereo Jack for Audio
Output terminals	5 x BNC (RGBHV,Y-Pb/Cb-Pr/Cr) Component (Y-Pb-Pr) BNC (Video) Scart (RGB) RS232 (D-Sub 9 pin) 2 x RCA (R/L mono) for Audio External speaker output (2 x 6W)
Operating temperature	0 °C to +35 °C
Storage Temperature	-20 °C to +60 °C
Voltage	220 – 240 V (50Hz)
Power consumption	188 W / 1.2 W (Stand-by Mode)
Dimensions (W x H x D)	1,032 x 625 x 127 mm
Weight	22.5Kg
Vesa mounting sizes	400 x 400, 800 x 400 mm
Colour of cabinet	Black
Warranty	2 years
Standard accessories	User Manual, Remote control, Power Cable
Special features	Sunlight Readable- Adaptive brightness in accordance with prevailing light conditions, Anti reflective acrylic panel.



Technical specifications subject to change without notice. Date 04/2008

