



**FULL  
HD  
1080p**

## 52LH1WP



- Fully-approved IP66 weatherproof, protected against powerful water jets and dust ingress
- Screen dimensions: 132 cm (52 inch)
- Winter mode: -20 °C to +45 °C operation
- Robust screen surface with anti-reflective tempered glass
- Anti-corrosive anodized aluminium cabinet
- Ideally suited for various indoor and outdoor installations as well as 24/7 applications
- Extensive input & output terminals
- Impressive picture quality: HD Ready

# 52LH1WP

<b>Model</b>	<b>52LH1WP</b>
EAN Code	4994334246776
Category	Professional LCD monitor
Type	Liquid crystal display panel
IP rating	IP66*
Screen size (diagonal image)	42" (105 cm)
Active screen area (W x H)	93.0 x 52.3 cm
Aspect ratio	16 : 9
Resolution in pixels	1,366 x 768 (WXGA)
Pixel pitch	0.227 x 0.681 mm
Brightness	500 cd/m <sup>2</sup>
Contrast ratio	1,500 : 1
Viewing angle	178° (horizontal and vertical)
Response time	6 ms (gray to gray)
Grey scale value	8 bit
Number of colours	16.7 M
Colour Systems	PAL, NTSC3.58 (AV in), SECAM
Computer compatibility	UXGA/WXGA/SXGA/XGA/SVGA/VGA
Input terminals	DVI-D (digital/HDCP) D-Sub15 5 x BNC (RGBHV, Y-Pb/Cb-Pr/Cr) Component (Y, Pb, Pr) BNC (Video) Scart (RGB), Video RS232 (D-Sub 9 pin) 2 x RCA (R/L mono) for Audio 3.5 mm Stereo Jack for Audio
Output terminals	5 x BNC (RGBHV, Y-Pb/Cb-Pr/Cr) Component (Y, Pb, Pr) BNC (Video) RS232 (D-Sub 9 pin) 2 x RCA (R/L mono) for Audio External speaker output (2 x 6 W)
Operating temperature	-20 °C to +45 °C (winter mode)
Storage Temperature	-20 °C to +60 °C
Maximum resilience	100 N/mm <sup>2</sup>
Voltage	100-240 V (50/60 Hz)
Power consumption	200W / 2W (stand-by mode)
Dimensions (W x H x D)	1304 x 800 x 236 mm
Weight	74 kg
Vesa mounting sizes	997 x 140, 997 x 280, 997 x 420
Colour of cabinet	Silver
Warranty	2 years
Standard accessories	User manual, remote control, batteries, power cable
Optional accessories	Anti-corrosive wall mount (LCD 200), PJ Net Organizer Plus (POA-LN02)
Special features	Anodized aluminium case, weatherproof, reinforced, anti-reflective tempered glass screen surface, 24h/7 approved, portrait mode, extensive input & output terminals

\* IP = Protection class



Technical specifications subject to change without notice. Date 04/2008

