



PDG-DXT10L

- Native resolution: 1,024 x 768 (XGA), DLP
- Brightness: 5,200 ANSI lumens, contrast ratio: 2,100 : 1
- 24/7 approved
- Horizontal and vertical lens shift function
- Quick lens replacement and 5 optional lenses
- Adjustable up to 500-inch diagonal screen size
- 6-segment colour wheel available as optional accessory
- HDTV-compatible
- 3 years warranty

PDG-DXT10L

TECHNICAL DETAILS	PDG-DXT10L
Category	Professional
Panel	1 x 0.7" DMD Chip (4 : 3)
Lamp	2 x 260 W UHP (LMP-I17)
Brightness ANSI lumens	5,200
Lamp Service Life	2,500 h (eco mode)/2,000 h (normal mode)
Fan Noise	34 dB (eco mode)/36 dB (normal mode)
Standard Lens	Delivery without lens*
Throw Distance Ratio	Depending on lens*
Throw Distance	Depending on lens*
Contrast Ratio	2,100 : 1
Resolution in pixels	1,024 x 768 (XGA)
Image size min-max (diagonal)	40"-500"
Uniformity	85 %
Bandwidth/Frequency	170 MHz, horizontal 15, 31-90 kHz, vertical 50-85 Hz
Colour Systems	PAL/SECAM/NTSC/NTSC4.43/PAL-M/N
Connections	Input 1: D-Sub15 (RGB) Input : 5 x BNC (RGBHV/Y-Pb/Cb-Pr/Cr) Input 3: DVI-D (digital/HDCP) Input 4: 3 x RCA (Y-Pb/Cb-Pr/Cr) Input 5: Mini DIN 4-pin (S-Video) Input 6: D-Sub 15 monitor output Audio: 3.5 mm Stereo Jack (for Computer), 2 x RCA (R/L mono) for video Audio Output: 3.5 mm Stereo Jack (variable) Control Input Jack 1: D-Sub15 Control Input Jack 2: 3.5 mm Stereo Jack (cable remote control) Control Input Jack 3: D-Sub9 (RS232) Control Input Jack 4: LAN Input Control Input Jack 5: USB type B; Others: 3.5 mm Stereo Jack (screen trigger output)
Keystone Correction	vertical +/-40°, horizontal +/-35°
Lens-Shift	1 : 1 vertical (applies to LNS-W41) 1 : 1 - 10 : 0 vertical (applies to all other lenses) 1 : 1 horizontal (applies to LNS-W41) 2 : 3 - 3 : 2 horizontal (applies to all other lenses)
HDTV Signals	720p/1,080i (HDTV-compatible)
Computer Compatibility	UXGA/SXGA/SXGA+/WXGA/XGA/S-VGA/VGA/Mac
Zoom/Focus	Depending on lens
Power Consumption/Voltage	580 W (eco mode)/690 W (normal mode)/100-240 V
Warranty	3 years
Dimensions (W x H x D)	505 x 192 x 385 mm
Weight	16.5 kg
Standard Accessories	IR/cable remote control (incl. cable), batteries, user manual (CD-ROM), power cable, D-Sub 15 cable, PIN code label, lens cap, anti-theft screw for lens
Optional Accessories	6-segment colour wheel (POA-CW01)
Lenses	Optional standard lens: LNS-S40 (Throw distance ratio: 1.78-2.35 : 1) Optional Wide angle lens: LNS-W40 (Throw distance ratio: 1.33-1.79 : 1) Optional Extreme wide angle lens: LNS-W41 (Throw distance ratio: 0.77 : 1) Optional tele zoom lens: LNS-T40 (Throw distance ratio: 2.22-4.43 : 1) Optional extreme tele zoom lens: LNS-T41 (Throw distance ratio: 4.4-8.3 : 1)

* You can use the distance calculator at www.sanyo.co.uk to determine exact image sizes and distances



Technical specifications subject to change without notice. Status 09/2007

