



## PLC-WXE46

- Brightness: 2000ANSI Lumen
- Resolution: WXGA (1280 x 800)
- Fixed Short Throw Projector, 80" @ 86cm
- Aspect Ratio's: 16:10, 16:9, 4:3
- Network Control and Monitoring
- 2 Data, 2 Video inputs

## PLC-WXE46

TECHNICAL DETAILS	PLC-WXE46
Category	Education
Panel	3 x 0.59" Polysilicon TFT active Matrix (16:10)
Lamp	200W UHP
Brightness ANSI lumens	2000
Lamp Service Life	3000h (Eco Mode), 1500h (Normal Mode)
Fan Noise	31dBA (Eco Mode), 38dBA (Normal Mode)
Standard Lens	F=1.8, f=6.6mm
Throw Distance Ratio	80" image @ 86cm
Throw Distance	0.53 – 1.20m
Contrast Ratio	500:1
Resolution in pixels	1,024,000 (1280 x 800)
Image size min-max (diagonal)	50" – 110"
Uniformity	80%
Bandwidth/Frequency	140MHz, Horizontal 15kHz – 100kHz, Vertical 50Hz – 100Hz
Colour Systems	NTSC, PAL, SECAM, NTSC4.43, PAL-M, PAL-N
Connections	Input: 2 x Dsub15 (Analog RGB, Component) 1 x Switchable 1 x Mini Din 4-Pin (S-Video) 1 x RCA (Composite Video) 1 x Mini Jack (Audio Input) 2 x RCA (Audio Input) Output: 1 x Dsub15 (Monitor out, Switchable) 1 x Mini Jack (Audio Out) Control: 1 x Mini Din 8-Pin (RS232) 1 x RJ45 (LAN)
Keystone Correction	Vertical $\pm 20^\circ$
HDTV Signals	1080i/50, 1080i/60, 720p
Computer Compatibility	UXGA, WXGA, SXGA+, SXGA, XGA, SVGA, VGA, MAC
Zoom/Focus	Fixed / Manual
Power Consumption/Voltage	190W (Eco Mode), 250W (Normal Mode), 7.5W (Standby Mode)
Warranty	3 year
Dimensions (W x H x D)	319.9 x 148.4 x 300.9mm
Weight	3.4kg
Standard Accessories	Quick Reference Guide, Owners Manual (CD ROM), Power Cable, Computer Cable (Dsub15 – Dsub15), Remote Control
Optional Accessories	POA-CA-COMPVGA (Component – VGA Cable), POA-CA-SCART (Scart – VGA Cable), POA-MCSRL (Dsub9 – Mini DIN 8-Pin cable)

\* You can use the distance calculator at <http://uk.sanyo.com> to determine exact image sizes and distances



Technical specifications subject to change without notice. Status 07/2009



Telephone: 01923 246363

Email: [info@sanyo.co.uk](mailto:info@sanyo.co.uk)

Visit: <http://uk.sanyo.com>