



## PLC-WXU300

- Brightness: 2500 ANSI Lumen
- Resolution: WXGA (1280 x 800)
- HDMI input for Digital Video or Data
- 7w Built in Speaker and Amplifier
- 1.6x Short Throw Lens
- Auto Setup: Input Search, PC Adjust and Keystone correction
- Picture in Picture (PIP) and Picture by Picture (PAP)
- Network Control and Monitoring

## PLC-WXU300

TECHNICAL DETAILS	PLC-WXU300
Category	Business and Education
Panel	3 x 0.59" Polysilicon TFT active Matrix LCD
Lamp	225W UHP
Brightness ANSI lumens	2500
Lamp Service Life	2500h (Eco Mode), 2000h (Normal Mode)
Fan Noise	29dBA (Eco Mode), 34dBA (Normal Mode)
Standard Lens	F= 1.65 - 2.33, f = 15.47mm – 24.53mm
Throw Distance Ratio	1.18 – 1.91:1
Throw Distance	0.74m – 7.67m
Contrast Ratio	500:1
Resolution in pixels	1,024,000 (1280 x 800)
Image size min-max (diagonal)	30 – 300"
Uniformity	85%
Bandwidth/Frequency	140MHz, Horizontal 15kHz – 100kHz, Vertical 50Hz – 100Hz
Colour Systems	NTSC, PAL, SECAM, NTSC4.43, PAL-M, PAL-N
Connections	Inputs: Dsub 15 x 2 (Component/ Scart RGB, 1 Switchable) HDMI x 1 (Digital) RCA x 1 (Composite Video) Mini DIN 4 Pin (S-Video) Mini Jack x 2 (Audio Input) RCA x 2 (Audio Input) Output: Dsub 15 x 1 (Monitor out, Switchable) Mini Jack x 1 (Audio Out, Variable) Control: Dsub 9 x 1 (RS232 Control) RJ45 (Wired LAN)
Keystone Correction	Vertical $\pm 30^\circ$
HDTV Signals	1080p, 1080i, 720p
Computer Compatibility	WUXGA, WSXGA+, WXGA+, WXGA, UXGA, SXGA+, SXGA, XGA, VGA
Zoom/Focus	1.6x / Manual
Power Consumption/Voltage	213W (Eco Mode), 291W (Normal Mode), 0.8W (Standby Mode)
Warranty	3 Year
Dimensions (W x H x D)	326 x 83.1 x 231.6mm
Weight	2.8Kg
Standard Accessories	Quick Reference Guide, User Manual (CD ROM), Computer Cable (Dsub 15 – Dsub 15), Power Cable, Remote Control, Soft Carry Bag.
Optional Accessories	POA-CA-COMPVGA (Component – Dsub 15 Cable), POA-CA-SCART Scart – Dsub 15 Cable)

\* You can use the distance calculator at <http://uk.sanyo.com> to determine exact image sizes and distances



Technical specifications subject to change without notice. Status 07/2009



Telephone: 01923 246363

Email: [info@sanyo.co.uk](mailto:info@sanyo.co.uk)

Visit: <http://uk.sanyo.com>