



PLC-XC50

- Brightness: 2600 ANSI
- Resolution 1024 x 768 (XGA)
- 7W (RMS) Built in speaker and amplifier
- Active maintenance filter (AMF)
- Easy lamp access (top cabinet)
- Security Bar (Will allow up to an 11mm cable)
- Auto Set up

PLC-XC50

TECHNICAL DETAILS	PLC-XC50
Category	Business & Education
Panel	3 x 0.6" TFT p-Si (4:3)
Lamp	220 W UHP
Brightness ANSI lumens	2,600
Lamp Service Life	3,000 h (Eco Mode)
Fan Noise	27.5 dB
Standard Lens	F = 1.60-1.76/ f = 22.3 -26.80
Throw Distance Ratio	1.72 – 2.07:1
Throw Distance	1.4-12.7 m
Contrast Ratio	450:1
Resolution in pixels	1024 x 768 (XGA)
Image size min-max (diagonal)	40" – 300"
Uniformity	85%
Bandwidth/Frequency	140MHz, horizontal 15kHz ~ 100kHz, vertical 50Hz ~ 100Hz
Colour Systems	NTSC / PAL / SECAM / NTSC4.43 / PAL-M / PAL-N
Connections	Input 1: DVI-I Input 2: D-sub 15 Input 3: S-video Input 4: RCA Audio Input: 2 x Minijack, 2 x RCA Control: Mini Din 8pin Output: D-sub 15 Audio Out: Mini Jack
Keystone Correction	vertical +/- 20°
Up/Down Ratio	9 : 1
HDTV Signals	1080i/50, 1080i/60, 1035i, 720p
Computer Compatibility	UXGA / WXGA / SXGA+ / SXGA / XGA / SVGA / VGA / MAC
Zoom/Focus	1.2 X / Manual
Power Consumption/Voltage	205w (Eco mode), 281w (Normal mode), 3.7w (Eco Standby mode), 6.8w (Normal standby)
Warranty	3 years
Dimensions (W x H x D)	410 x 11.2 x 266.8 mm
Weight	4.0kg
Standard Accessories	Quick Ref Guide, Owner manual (CD ROM), Power Cable, computer cable(D-sub 15-D-sub 15), Remote control
Optional Accessories	POA-CA-COMPVGA (3RCA – D-sub 15), POA-CA-SCART (SCART- D-sub 15)

* You can use the distance calculator at www.sanyo.co.uk to determine exact image sizes and distances



Technical specifications subject to change without notice. Status 09/2007



Telephone: 01923 246363

Email: info@sanyo.co.uk

Visit: www.sanyo.co.uk