



PLC-XC56

- Brightness: 3100ANSI lumen
- Resolution: XGA (1024 x 768)
- 7w (RMS) built in speaker and amplifier
- Active Maintenance Filter
- Network Control and Monitoring
- Security Bar (Will allow up to an 11mm cable)
- Auto Set up

PLC-XC56

TECHNICAL DETAILS	PLC-XC56
Category	Business & Education
Panel	3 x 0.63" TFT p-Si (4:3)
Lamp	220w UHP
Brightness ANSI lumens	3100
Lamp Service Life	4000h (Eco Mode), 2000h (Normal Mode)
Fan Noise	27.5dBA (Eco Mode), 34dBA (normal Mode)
Standard Lens	F= 1.60 – 1.76, f=22.33 – 26.80mm
Throw Distance Ratio	1.72 – 2.07:1
Throw Distance	1.4 – 12.7m
Contrast Ratio	450:1
Resolution in pixels	1024 x 768 (XGA)
Image size min-max (diagonal)	40 – 300"
Uniformity	85%
Bandwidth/Frequency	140MHz, Horizontal 15kHz – 100kHz, Vertical 50Hz – 100Hz
Colour Systems	NTSC, PAL, SECAM, NTSC4.43, PAL-M, PAL-N
Connections	Inputs: 1 x DVI-I 1 x Dsub15 (RGB) 1 x Mini Din 4-pin (S-Video) 1 x RCA (Composite Video) Audio In: 2 x Mini Jack 2 x RCA Outputs: 1 x Dsub15 (Monitor Out) Audio Out: 1 x Mini Jack Control: 1 x Dsub9 (RS232) 1 x RJ45 (LAN Control)
Keystone Correction	Vertical $\pm 20^\circ$
HDTV Signals	1080i/50, 1080i/60, 1035i, 720p
Computer Compatibility	UXGA, WXGA, SXGA+, SXGA, XGA, SVGA, VGA, MAC
Zoom/Focus	1.2x / Manual
Power Consumption/Voltage	205w (Eco Mode), 290w (Normal Mode), 0.9w (Standby Mode)
Warranty	3 year
Dimensions (W x H x D)	410 x 111.2 x 266.8 mm
Weight	4.1kg
Standard Accessories	Quick Ref Guide, Owners Manual (CD ROM), Power cable, Computer Cable (Dsub15 – Dsub15), Remote Control
Optional Accessories	POA-CA-COMPVGA (3 RCA – Dsub15), POA-CA-SCART (Scart – Dsub15),

* You can use the distance calculator at www.sanyo.co.uk to determine exact image sizes and distances



Technical specifications subject to change without notice. Status 11/2009

