



## PLC-XL50

- XGA Resolution (1024 x 768)
- 2000 ANSI Lumen
- 600:1 Contrast Ratio
- Digital Keystone Correction
- Ultra Short Throw Lens (80" Diagonal Screen @ 9cm Throw Distance)
- Antitheft Alarm
- Auto Input Search

## PLC-XL50

TECHNICAL DETAILS	PLC-XL50
Category	Business & Education
Panel	0.8 inch TFT p-Si x 3
Lamp	Single 275W Lamp
Brightness ANSI lumens	2,000
Fan Noise	25 dB (eco mode)/30 dB (normal mode)
Standard Lens	$F = 1.65-1.83 / f = 22.5-27.0 \text{ mm}^*$
Contrast Ratio	600 : 1
Resolution in pixels	2,359,296 (1024 x 768 dots)
Uniformity	80%
Bandwith/Frequency	H/V sync ~ 15-100kHz ~ 50-100Hz, Dot clock 140 MHz
Colour Systems	PAL / SECAM / NTSC / NTSC4.43 / PAL-M/N
Connections	Input 1: 1 x Dsub 15 Input 2: 1 x Dsub 15 (Switchable) Input 3: 3 x RCA (Component), S Video 1 x RCA (Composite) Audio Out: Computer: Minijack stereo. Communication Terminal: RS232C (Mini DIN 8 Pin)
Keystone Correction	vertical +/- 5°
Computer Compatibility	UXGA/ SXGA+ / SXGA/ WXGA/ SVGA/ VGA/ MAC
Power Consumption/Voltage	100V-240V AC (auto voltage)
Warranty	3 years
Dimensions (W x H x D)	374 x 196.8 x 495 mm
Weight	7.6kg

\* You can use the distance calculator at [www.sanyo.co.uk](http://www.sanyo.co.uk) to determine exact image sizes and distances



Technical specifications subject to change without notice. Status 09/2007

