



PLC-XL51

- Brightness: 2700 ANSI Lumen
- Durable Optical Engine (Inorganic LCD)
- Ultra Short Throw (80" Diagonal screen @ 9cm Throw)
- Resolution: XGA (1024 x 768)
- Contrast: 1200 : 1
- SD Memory Card Reader
- Built in Networkability (Wired/Wireless)
- Built in audio Amplifier and speaker
- Anti-theft Alarm
- Pin code Security

PLC-XL51

TECHNICAL DETAILS	PLC-XL51
Category	Business & Education
Panel	0.8 inch TFT p-Si x 3
Lamp	Single 275W NSHA
Brightness ANSI lumens	2,700
Lamp Service Life	3000h (Eco Mode), 2000h (Normal Mode)
Fan Noise	32.6 dBA (Eco Mode), 36.9 dBA (normal Mode)
Standard Lens	F= 1.85, f= 4.83mm
Throw Distance Ratio	80" diagonal @ 8.1cm
Throw Distance	-4cm to 8cm
Contrast Ratio	1,200 : 1
Resolution in pixels	2,359,296 (1024 x 768)
Image size min-max (diagonal)	60" - 80"
Uniformity	80%
Bandwidth/Frequency	140MHz, Horizontal 15kHz - 100kHz, Vertical 50Hz - 100Hz
Colour Systems	NTSC / PAL / SECAM / NTSC4.43 / PAL-M / PAL-N
Connections	Input 1: 1 x Dsub 15 (RGB/ Scart RGB) Input 2: 1 x Dsub 15 (RBG in or monitor out) Input 3: 1 x S-Video Input 4: 3 x RCA (Component Video) Input 5: 1 x RCA (Composite Video) Audio in: 2 x RCA Network: RJ45 (for LAN Port) SD Card Reader Control: 1 x Mini 8 pin DIN
Keystone Correction	Vertical $\pm 5^\circ$
HDTV Signals	1080i/50, 1080i/60, 1035i, 720P
Computer Compatibility	UXGA / WXGA / SXGA+ / SXGA / XGA / SVGA / VGA / MAC
Zoom/Focus	Manual
Power Consumption/Voltage	340W (Eco mode), 400W (Normal mode), 12W (Standby mode)
Warranty	3 Year
Dimensions (W x H x D)	374 x 196.8 x 495mm
Weight	7.7kg
Standard Accessories	Quick Reference Guide, Owners Manual (CD ROM), Power Cable, Remote Control, Computer Cable (Dsub15-Dsub15), Network (CD ROM)
Optional Accessories	SST Bracket-WH (Wall Mount bracket), POA-CA-SCART (Scart-VGA Cable)

* You can use the distance calculator at www.sanyo.co.uk to determine exact image sizes and distances



Technical specifications subject to change without notice. Status 11/2008

