



PLC-XU105

- Resolution Native: 1024 x 768 (XGA)
- Brightness: 4500 ANSI
- 360 Projection
- Auto Input Search
- Pin Code Security
- 3 years warranty

PLC-XU105

TECHNICAL DETAILS	PLC-XU105
Category	Business and Education
Panel	3 x 0.8" TFT p-si(4:3)
Lamp	275 W NSHA (LMP 111)
Brightness ANSI lumens	4500 (normal mode) 3600 ANSI (eco mode)
Lamp Service Life	3000h (eco mode) 2000h (normal mode)
Fan Noise	31 dBA (eco mode) 39 dBA (normal mode)
Standard Lens	F= 1.7 - 2.5 / f= 19.2 - 30.2mm
Throw Distance Ratio	1.15 - 1.85:1
Throw Distance	0.93 - 11.47m
Contrast Ratio	500:1
Resolution in pixels	1024 x 768 (XGA)
Image size min-max (diagonal)	40" - 300"
Uniformity	85 %
Bandwidth/Frequency	140MHz, Horizontal 15kHz - 100 kHz, Vertical 50Hz - 100Hz
Colour Systems	NTSC / PAL / SECAM / NTSC4.43 / PAL-M / PAL-N
Connections	Input 1: D-sub 15 (RGB) Input 2: D-sub 15 (RGB, Component, Scart RGB), Mini Jack (Audio Input) Input 3: Mini DIN 4 pin (S-Video) Input 4: RCA (Composite Video), RCA x 2 (Audio Input) Control: Mini DIN 8 pin, (serial Control) Monitor Output: D-sub 15 Audi Out: mini Jack
Keystone Correction	Vertical $\pm 40^\circ$
U/D Ratio	9:1
HDTV Signals	480i / 480p / 575i / 575p / 720p / 1080i
Computer Compatibility	UXGA / WXGA / SXGA+ / SXGA / XGA / SVGA / VGA / MAC
Zoom/Focus	1:1.6 / Manual
Power Consumption/Voltage	266 W (eco mode) 332 W (normal mode)
Warranty	3 years
Dimensions (W x H x D)	334 x 93 x 257.5 mm
Weight	3.5 kg
Standard Accessories	Quick set up manual, CD Rom, Computer cable (Dsub 15-Dsub 15), Serial Control Cable (Mini DIN8 -Dsub 15), Remote Control, Soft carry bag
Optional Accessories	Component-Dsub 15 (POA-CA-COMPVGA)

* You can use the distance calculator at www.sanyo.co.uk to determine exact image sizes and distances



Technical specifications subject to change without notice. Status 09/2007

