



## PLC-XU115

- Resolution Native: 1024 x 768 (XGA)
- Brightness: 4500 ANSI
- 360 Projection
- Network Integration With LAN Connector (RJ45) and WLAN
- SD Card Reader
- Auto Input Search
- 3 years warranty

## PLC-XU115

TECHNICAL DETAILS	PLC-XU115
Category	Business and Education
Panel	3 x 0.8" TFT p-si(4:3)
Lamp	275 W NSHA (LMP 111)
Brightness ANSI lumens	4500 (normal mode) 3600 ANSI (eco mode)
Lamp Service Life	3000h (eco mode) 2000h (normal mode)
Fan Noise	31dBA (eco mode) 39dBA (normal mode)
Standard Lens	F= 1.7 - 2.5 / f= 19.2 - 30.2mm
Throw Distance Ratio	1.15 - 1.85:1
Throw Distance	0.93 - 11.47m
Contrast Ratio	500:1
Resolution in pixels	1024 x 768 (XGA)
Image size min-max (diagonal)	40" - 300"
Uniformity	85 %
Bandwidth/Frequency	140MHz, Horizontal 15kHz - 100 kHz, Vertical 50Hz - 100Hz
Colour Systems	NTSC / PAL / SECAM / NTSC4.43 / PAL-M / PAL-N
Connections	Input 1: DVI-I (HDCP) Input 2: D-sub 15 (RGB, Component, Scart RGB), Mini Jack (Audio Input) Input 3: Mini DIN 4 pin (S-Video) Input 4: RJ45 Input 5: Wireless Network Input 6: SD Card Reader Control: Mini DIN 8 pin, USB type B, Mini Jack (for wired R/C) Monitor Output: D-sub 15 (Analogue RGB signal monitor out) Audio Out: mini Jack
Keystone Correction	Vertical $\pm 40^\circ$
U/D Ratio	9:1
HDTV Signals	480i / 480p / 575i / 575p / 720p / 1080i
Computer Compatibility	UXGA / WXGA / SXGA+ / SXGA / XGA / SVGA / VGA / MAC
Zoom/Focus	1:1.6 / Manual
Power Consumption/Voltage	269 W (eco mode) 335 W (normal mode)
Warranty	3 years
Dimensions (W x H x D)	334 x 93 x 257.5 mm
Weight	3.6 kg
Standard Accessories	Quick set up manual, CD Rom, Computer cable (Dsub 15-Dsub 15), Serial Control Cable (Mini DIN8 -Dsub 15), Remote Control, Soft carry bag
Optional Accessories	Component-Dsub 15 (POA-CA-COMPVGA), Dsub 15-DVI (POA-CA-DVIVGA)

\* You can use the distance calculator at [www.sanyo.co.uk](http://www.sanyo.co.uk) to determine exact image sizes and distances



Technical specifications subject to change without notice. Status 09/2007

