



**HD
ready**

PLC-WXU700

- Brightness: 3800 ANSI Lumen
- Resolution: WXGA (1280 x 800)
- Vista Compatible
- Network Viewer and Capture with Easy Wireless (802.11n)
- Will play moving images via it's "video streaming function"
- USB Memory Viewer
- HDMI for Digital Data and Video inputs
- 2 x Data and 2 x Video Analogue Inputs
- Auto setup (Input search, keystone correction, PC adjust)
- Picture in Picture / Picture By Picture
- 1.6x short throw zoom lens

PLC-WXU700

TECHNICAL DETAILS	PLC-WXU700
Category	Business & Education
Panel	3 x 0.74" TFT Polysilicon (16:10), Micro lens
Lamp	275W NSHA
Brightness ANSI lumens	3800
Lamp Service Life	3000h (Eco Mode), 2500 (Normal Mode), 2000h (High Mode)
Fan Noise	31dBA (Eco Mode), 35dBA (Normal Mode), 38dBA (High Mode)
Standard Lens	F= 1.7-2.5, f= 19.2-30.2mm
Throw Distance Ratio	1.17-1.87:1
Throw Distance	0.99 – 12.1m
Contrast Ratio	500:1
Resolution in pixels	1,024,000 (1280 x 800)
Image size min-max (diagonal)	40" – 300"
Uniformity	85%
Bandwidth/Frequency	140MHz, Horizontal 15kHz – 100kHz, Vertical 50Hz – 100Hz
Colour Systems	NTSC / PAL / SECAM / NTSC4.43 / PAL-M / PAL-N
Connections	Inputs: 2 x D-sub15 (Component/Scart RGB) 1 x HDMI (Digital) 1 x Mini DIN 4-pin (S-Video) 1 x RCA (Composite Video) 1 x RJ45 (Wired LAN) 1 x USB-A (Memory Viewer) Audio: 2 x Mini Jack 2 x RCA Output: 1 x D-sub15 (switchable) Audio: 1 x Mini Jack (Audio out) Control: 1 x D-sub9 1 x USB-B (Mouse Control) 1 x Mini Jack (Wired RC)
Keystone Correction	Vertical $\pm 20^\circ$
HDTV Signals	480p, 575p, 720p (50/60), 1080i (50/60), 1080p (50/60)
Computer Compatibility	WUXGA / WSXGA+ / WXGA+ / WXGA / UXGA / SXGA+ / SXGA / XGA / SVGA / VGA
Zoom/Focus	1.6x / Manual
Power Consumption/Voltage	278w (Eco Mode), 316w (Normal Mode), 345w (High Mode) 12.1w (Standby)
Warranty	3 Year
Dimensions (W x H x D)	335.7 x 93.9 x 257.5mm
Weight	3.6kg
Standard Accessories	Quick Reference Guide, User Manual (CD ROM), Power Cable, Computer Cable (D-sub15), Remote Control & Batteries, Network Software (CD ROM), Easy Wireless USB, Soft Carry Bag
Optional Accessories	POA-CA-COMPVGA (Component – D-sub15), POA-CA-SCART (Scart – D-sub15)

* You can use the distance calculator at <http://uk.sanyo.com> to determine exact image sizes and distances



Technical specifications subject to change without notice. Status 06/2009



Telephone: 01923 246363

Email: info@sanyo.co.uk

Visit: <http://uk.sanyo.com>